BT0305.02 SPECIFICATIONS

azure-2 blu-stone™ freestanding bathtub

FEATURES:

- Freestanding, blu•stone™ bathtub
- Streamlined, high profile one piece design
- 67" (1700mm) L x 311/2" (800mm) W x 193/4" (500mm) H
- Includes integral slot overflow & matching blu·stone™ waste cover
- Made of blu stone™ providing the look and feel of natural stone
- Stronger and more durable than acrylic
- Non-porous, stain resistant surface that does not require sealing
- Does not promote bacteria, mold or fungi
- Tailpiece not included (Blu recommends BTWaste.RN or BTWasteCl.RN)

SPECIFICATIONS:

Basin Area: 481/4" (1225mm) x

25" (635mm)*

Top Area: 63¾" (1620mm) x

291/2" (750mm)*

To Overflow: 21/4" (60mm)*

Slope of Backrest: 30°*

Water Depth: 141/4" (365mm)*
Capacity: 82G (310L)*
Weight: 430lbs (195kg)*

Hot water supply req'd: Should be 70% of water

capacity of tub or greater

Warranty: Five Year Warranty (Residential use)

One Year Warranty (Commercial use)

Material: blu·stone™ Shipping Weight: 562lbs (255kg)*

Shipping Dimensions (LWH) 69%" x 341/4" x 203/4" (1770mm x 870mm x 530mm)*

COLORS/FINISHES:

White Matte or Gloss as standard

Available in a range of blu·stone[™] colors + finishes (special order)

ACCESSORIES (sold separately):

- BTWaste.RN or BTWasteCl.RN Island tub drain for easy installation

INSTALLATION NOTES:

Install this product according to the installation guide. Floor support under bath must provide for a minimum of 1400 lbs (635kg). Installation will vary. Our products must be installed by certified professionals only and according to our installation guide as well as federal, provincial / state and local building codes and regulations

CODES / STANDARDS APPLICABLE:

- Meets or exceeds ANSI / ASME standard CSA B45.5.11 / IAPMO Z124
- IAPMO / ANSI Z124.8
- CSA



*Approximate measurements for comparison only.

Note: These dimensions and specifications are subject to change without notice.









