

POETTO

MAIN KITCHEN FAUCET

Features


- Solid brass construction
- High-arc 360° rotating spout allows for easy filling of large pots and cleaning
- Magnetic docking secures sprayhead into spout
- One button brass sprayhead has dual function aerated or spray mode Spray jets have easy-to-clean surface that withstands mineral build-up
- Quiet polymer-braided hose with rotating joint at sprayhead allows for smooth and non-binding use

- Ceramic disc cartridge
 1.8 gpm (6.8 L/min) max flow rate
 Over 30 finishes including 15 PVD finishes

Codes/Standards Applicable

Meets or exceeds the following at date of manufacture:
• ASME A112.18.1/CSA B125.1

- NSF 61 and NSF 372



XX = DENOTES HANDLE STYLE

	DIME	NCION	IC (in)					THROUG	GH-HOLE SPECIF	ICATIONS
XX	A	NSION B	C (In.)	D	E			MIN	RECOMENDED	MAX
HANDLE								Ø 1-1/4"	Ø 1-3/8"	Ø1-9/16
ST	$7\frac{9}{16}$	$3\frac{7}{16}$	6 <u>11</u>	2 <mark>15</mark>	5 13					
BST	7 9 16	3 7 16	$6\frac{11}{16}$	2 15 16	5 13 16		10 $\frac{7}{8}$ "		-	
SST	6	$2\frac{13}{16}$	5 9 16	1 5 8	3 16					T
BSST	6	2 <mark>13</mark>	5 9 16	1 5 8	3 16					
								//	\	
									1	
						0			18	
						B B	9 3 16"	-	 E	
						22°	, , ,		- D	
							C.	50°	100°	
							10 16"			
		0	15	A.V				\bigcap		
		(WIT	16 MA H SPA	AX _ (CER)		$3\frac{1}{2}$ "	Ø2 3 " —			
	_						V 16			
		3-	5 <mark>8</mark> " MA S SPA	X						
		(LES	Š SPA	CER)	<u></u>	3 7 16 "	2 1 —	-	 	9 3 "
					-	2 <u>1</u>	2 1 " —	-	<u></u>	
							3/8" COMPRESSION	~ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	1 ^\	
							FITTING	_	1	