




SensoWash® i SensoWash® i Plus integrated shower-toilet $\ \#\ 620000011401320$

|< 14 1/2" Inch >|









SensoWash® i Plus integrated shower-toilet	Dimension	Weight	Order number
Rear-, Lady- and Comfortwash, vertical outlet, heated sea Intelligent energy-saving mode, warm air dryer, individua adjustment of water-, air- and seat surface temperature as nozzle position and jet strength, odor extraction, Autonodor extraction, Adjustable odor extraction follow-up time flush, with integrated flushing system, pre-flush, automatopening/closing of lid, Electronically actuated lid, descaling function, night light, 2 individually programmable user promote control included, App operation, self-cleaning ward off-button, 17 3/8" Inch	l as well natic e, Auto tic ng ofiles,		
Colors			
00 White			
Variant			
AC 100-120V, 50-60 Hz, panels White, rimless, seat/lid material duroplast/thermoplastic $14\ 1/2$ " x 20		105.8 lb	620000011401320
Suitable spareparts			
Wall bracket frame type, for permanent remote control installation, suitable for SensoWash Plus remote control,			100724

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.