

PVC SYSTEMS INCLUDE:

- 8 Fully directional adjustable PVC jets
- Anti-vortex safety suction
- Color matched system trim
- HydroOzone ozone sanitation system
- Rigid PVC piping
- Self draining pump and system
- Soft Touch electronic on/off control with 20-minute integral times
- 2.25 HP single speed pump
- Cable waste and overflow
- Whirlpool system requires 20 Amp Dedicated GFCI 120V







OPTIONS

- *Colonial Grab Bars
- *Linear Integral Waste and Overflow
- *Chromatherapy-LED Lighting System
- Universal Grab Bars
- Microban Antibacterial Protection
- Extra high density fiberglass
- Custom jet and pump locations
- Waterfall Fill Spout (recirculating option available)
- Plated Metallic finish
- Additional directional Jets / Swirling
- Jumbo Jets rotating and directional

- Micro Therapy Jet
- Integral Waste and Overflow (round)
- Electronic low water protection
- In-line heater
- Back Masseuse
- Neck Masseuse Pillow
- Hydro Fusion
- Hydro Coat
- Indulge
- Hydro Express quick ship
- Digital LCD temperature display
- Hydro Blanket





OPTION	ELECTRICAL REQUIREMENTS
Whirlpool	1 20amp - 115V dedicated GFCI
Thermal Air	1 15amp - 115V dedicated GFCI
Combo	1 20amp - 115V & 1 15amp - 115V dedicated GFCI
Hydro Indulge	1 15amp - 115V dedicated GFCI
Inline Heater 1500	1 15amp - 115V dedicated GFCI
Inline Heater 600W	Shares circuit with Whirlpool pump
Fusion 1500W	1 15amp - 115V dedicated GFCI
Fusion 600W	1 15amp - 115V dedicated GFCI





As Shown:

Whirlpool option with standard jet location

FEATURES SHOWN:

- Jets
- Overflow location

AVAILABLE SYSTEMS:

- Soaking tub only
- Whirlpool
- Thermal Air
- Combo

SIZE:

74.42.22

WATER CAPACITY:

80 Gallons

WEIGHT:

80 - 120 Pounds

Model 7442 Dimensions:

- (L)ength-74"
- (W)idth- 42"
- (H)eight Finish- 22"
- Back Slope 29°

CUT-OUT DIMENSIONS:

- (L)ength-72"
- (W)idth- 40"
- (H)eight Finish- 21.25"

3-WALL DIMENSIONS:

- (L)ength-74"
- (W)idth- 42"
- Ledger 21.25"

CODES AND COMPLIANCES

Massachusetts code File no: P1-0614-491















ACRYLIC TUB

- Acrylic models finished in 1/8" thick layer of deep lustrous acrylic
- Extra thick reinforced fiberglass
- Pre-wired pump on pump platform (standard pump location only)
- Integral E-Z level platform facilitates installation
- Tub must be set in mortar base
- When adding linear option, p-trap located below waste

