

Buy it for looks. Buy it for life.®

DESCRIPTION

- Metal construction with chrome finish
- Flexible supply lines with 3/8" compression fittings
- Includes metal pop-up waste assembly

OPERATION

- · Lever style handle
- Temperature controlled by 100° arc of handle travel
- Includes hot & cold temperature indicators

FLOW

• Flow is limited to 1.2 gpm max (5.7L/min) at 60 psi

CARTRIDGE

• 1255™ Duralast™ cartridge for Single-Handle Faucets


STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1, NSF 61/9 & 372 and all applicable requirements referenced therein
- Third party certified to comply with WaterSense® High Efficiency Bathroom Sink Faucet Specification
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA for lever handle

WARRANTY

 Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser

Specifications



Via™ Single-Handle Lavatory Faucet

Model: \$8001

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 1 HOLE, 1-1/8" MIN. DIA.



6-7/64"

(155mm) 5 year warranty if used in commercial installations 2-59/64" (47mm) For lift rod operation 2-1/2" (63mm) min. from blackspash (152mm) 3-51/64" 3-15/32" 4-33/64" (96mm) (88mm) (115mm) 1-25/32" 2-25/32" (45mm) (71mm) 9 Degrees 2-3/64" 2-1/2" (52mm) (80mm) MAX. 23-1/4" (593mm) Lift Rod

CRITICAL DIMENSIONS
(DO NOT SCALE)