

MODEL DESCRIPTION

HousePure® Secure Tankless Water Heater Protection Part # WI-HP-SECURE-1.50L (water entry left side) Shipping Wt: 19 lbs.
 Part # WI-HP-SECURE-1.50R (water entry right side)
 Utilizing Siliphos Polyphosphate
 Recommended for all Tankless Water Heater Manufacturers



LEVEL 2 High Flow Tankless Water Heater Scale Prevention. Provides annual protection against costly water heater scaling and sediment build-up. Polyphosphate media prevents (sequesters) water hardness from scaling on flash heating surfaces. A dual-gradient 50 over 5 micron filter reduces sediment, which can cause additional scaling throughout the hot water line. The gradient density filter design provides up to three times the dirt-holding capacity of similar size sediment cartridges. The unique micro-fiber filter construction delivers higher filtration efficiency and flow rates. Ideal for indoor and outdoor installations. Features a 1-1/2" NPT inlet/outlet with a pressure-change gauge for peace-of-mind.

Includes powder-coated mounting bracket, filter gauge, & filter-change spanner wrench

Max Descaling Flow Rate: 20 gallons/minute

Dimensions: Width: 7.5" Height: 29" Depth: 8.75"

Filter Capacity: One year or when gauge indicates change needed

Water Temperature Range: 40°F to 100°F

Tools Required: Teflon® tape (do **not** use pipe dope), adjustable wrench, tube cutter, suitable pipe fittings, and inlet gate valve



NEW
 Water entry RIGHT side
WI-HP-SECURE-1.50R

Water, Inc filter change indicator included
 Component Tested to NSF/ANSI Standard 42
 for material requirements.

NEW
 Water entry RIGHT side
WI-HP-SECURE-1.50R

HousePure® Secure Replacement Cartridge Part # WI-HP-SECURE-1.50C Shipping Wt: 4 lbs.
 Utilizing Siliphos Polyphosphate Shipping Wt: 23 lbs.
 Recommended for all Tankless Water Heater Manufacturers



Capacity: One year or when gauge indicates change needed

Dimensions: Height: 20" Diameter: 4.5"

Replacement Cartridge for HousePure® Secure 1-1/2" tankless water heater filter system. The dual-gradient 50 over 5 micron filter with polyphosphate scale reducing media provides consistent flow rates and superior filtration performance.

The HousePure® Secure cartridge should be changed annually or when gauge indicates a change is needed sooner.

Tested to NSF/ANSI Standard 42 for material requirements.

Water, Inc filter change indicator included

 **MAXIMUM recommended line pressure for this product is 75 PSI.** Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283)